



Material Safety Data Sheet

Patriot Timber Products Int., Inc.

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Hardwood Plywood (Ultra Low Emitting-Formaldehyde)
Trade Name: Hardwood Plywood
Distributor: Patriot Timber Products Int., Inc.
Post Office Box 19065
Greensboro, NC 27419
PH: 336-299-7755
FAX: 336-299-4050
E-mail: support@patriottimber.com

Description: This panel product contains a hardwood veneer face bonded to wood components such as other wood veneer lumber or veneer strips using ultra low emitting - formaldehyde resin.

SECTION 2: COMPOSITION, INFORMATION OR INGREDIENTS

Component Formaldehyde (ULEF) CAS #50-00-0 - <0.1% by weight

Exposure Limit OSHA PEL TWA – .75 ppm
OSHA PEL STEL – 2 ppm
OSHA PEL ACTION LEVEL – 0.5 ppm
ACGIH TLV - CEILING – 0.3 ppm

CARB Phase 1 ≤ 0.08 ppm (2009)
CARB Phase 2 ≤ 0.05 ppm (2010)

Component Wood Dust - All species except Western Red Cedar

Exposure Limit OSHA PEL TWA – 15mg/m³ (Total Dust) 5.0mg/m³ (Respirable Fraction)
OSHA PEL STEL – 10mg/m³

ACGIH TLV (r) – TWA – 5.0mg/m³; STEL (15 min) – 10.0 mg/m³(Softwood); 1.0mg/m³ (Inhalable) (Certain hardwoods such as beech and oak)

SECTION 3: HAZARDS IDENTIFICATION

Eye Contact Gaseous formaldehyde may cause temporary irritation, mechanical irritation, or a burning sensation.

Skin Contact Both formaldehyde and various species of wood dust may evoke allergic contact dermatitis in sensitized individuals.

Ingestion Not likely to occur for product in purchased form.

Inhalation	May cause nasal dryness, irritation and obstruction. Coughing, wheezing and sneezing, sinusitis and prolonged colds have also been reported.
Chronic Effects:	
Formaldehyde	May cause nasal dryness, irritation and obstruction in nasal cavity and throat. Reports have shown formaldehyde may cause respiratory sensitization and may aggravate preexisting respiratory disorders. The United States EPA lists formaldehyde as a “B1 (Probable Human Carcinogen). Formaldehyde is regulated by OSHA as a potential cancer agent. National Toxicology Program (NTP) included formaldehyde in their Annual Report on Carcinogens
Wood Dust	Depending on the specie, may cause dermatitis on prolonged repetitive contact; may cause respiratory sensitization and/or irritation. Wood dust is listed in the National Toxicology Program (NTP) under the United States Department on Health and Human Services in the Report on Carcinogens (ROC) as known to be a human carcinogen since the 10 th RoC (2002).

SECTION 4: FIRST-AID MEASURES

Eyes	Remove contact lenses (if applicable). Flush eyes, including under eyelids, with large amounts of water and exit to fresh air. If irritation persists, get medical attention.
Skin	Wash affected area with soap and water. Get medical advice if a rash, persistent irritation or dermatitis occurs.
Inhalation	Exit to fresh air. Get medical advice if persistent irritation, severe coughing or breathing difficulty occurs.
Ingestion	Not applicable

SECTION 5: FIRE FIGHTING MEASURES

Flash Point	Not applicable
Autoignition Temperature	Dependent upon duration of exposure to heat source and other variables. 400 deg. – 500 deg. F (204 deg. – 260 deg. C).
Flammable Limits in Air	An airborne concentration of 40 grams of dust per cubic meter of air is often used as the lowest explosion limit (LEL) for wood dust. Formaldehyde Lower Explosion Limit (LEL) - 7% Upper Explosion Limit (UEL) - 73%
Unusual Fire & Explosion Hazards	Sawing, sanding or machining can produce wood dust as a by-product or “cloud” which may present a strong to severe explosion hazard if a dust particle contacts an ignition source.

Special Fire Fighting Properties	Burns like other wood products, but it is dangerous and may burn hotter. Partially burned dust is especially hazardous if dispensed into the air. Remove burned or wet dust to an open area after fire is extinguished. Wet down wood dust to reduce the likelihood of ignition or dispersion of dust into the air.
Extinguishing Media	Water, Carbon Dioxide, Sand

SECTION 6: ACCIDENTAL RELEASE MEASURES

Not applicable in purchased form. Sweep, shovel or vacuum dust from machined product for disposal. Wood dust cleanup and disposal activities should be accomplished in a manner to minimize creation of airborne dust.

*Notify appropriate regulatory agencies if accident does occur.

SECTION 7: HANDLING AND STORAGE

Store in a well-ventilated, cool, dry place allowing formaldehyde gas adequate ventilation to prevent possible build up, particularly when high temperatures occur.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation	Provide adequate general and local exhaust ventilation to keep airborne concentration levels below OSHA PEL's.
Other Types Controls	Due to the explosive potential of wood dust when suspended in air, precautions should be taken to prevent sparks or other ignition sources in ventilation system.
Personal Protective Equipment	Wear goggles or safety glasses when manufacturing or machining the product. Wear NIOSH/MSHA approved respirator when the allowable OSHA exposure limits may be exceeded. Other protective equipment such as gloves and outer garments may be needed to reduce skin contact depending on dust conditions.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	Not applicable
Specific Gravity (H₂O = 1)	<1.0
Vapor Density	Not applicable
% Volatiles by Vol.	0
Melting/Freeze Point	Not applicable
Vapor Pressure	Not applicable
Solubility in H₂O (% by wt.)	<0.1%
Evaporation Rate (Butyl Acetate = 1)	Not applicable
pH	Not applicable
Physical Form	Solid
Appearance, Color and Odor	Light to dark tan colored granular solid. Color and odor are dependent upon wood species.

SECTION 10: STABILITY AND REACTIVITY

Conditions Contributing to Instability Stable under normal conditions. Wood dust generated from sawing, sanding or machining is extremely combustible. Keep in cool dry place away from ignition sources.

Incompatibility Avoid contact with oxidizing agents and drying oils. Avoid open flame. Product may ignite in temperatures in excess of 400 degrees Fahrenheit.

Hazardous Decomposition Products Thermal oxidative decomposition can produce irritation and toxic fumes and gases, including carbon monoxide, hydrogen cyanide, aldehydes, organic acids and polynuclear aromatic compounds.

Hazardous Polymerization Not applicable

SECTION 11: TOXICOLOGICAL INFORMATION

Hardwood plywood may release small quantities of formaldehyde (CAS No. 50-00-0) in gaseous form. Emissions decrease through time as the panel ages. Exposure to formaldehyde may cause temporary irritation of eyes, nose and throat. Exposure can aggravate respiratory sensitization such as asthma and preexisting respiratory disorders.

Manual or mechanical cutting or abrasion processes performed on the product can result in generation of wood dust. Wood dust may cause nasal dryness, irritation and obstruction. Coughing, wheezing and sneezing, sinusitis and prolonged colds have also been reported.

Depending on species, wood dust may cause respiratory sensitization and/or irritation. Prolonged exposure to wood dust has been reported by some observers to be associated with nasal cancer, however; wood dust is not considered a potential cancer hazard by OSHA.

SECTION 12: ECOLOGICAL INFORMATION

Not applicable to product in purchased form.

SECTION 13: DISPOSAL CONSIDERATIONS

This product is not considered hazardous waste under federal hazardous waste Regulations 40 CFR 261. Your state and local government requirements may be different from the federal regulations. Incinerate or landfill waste in accordance with the local, state and federal regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT (Department of Transportation)
Hazard Class: Combustible

Proper Shipping Name: Hardwood Plywood (ULEF)
Identification Number: Not applicable

SECTION 15: REGULATORY INFORMATION

Toxic Substance Control Act Not applicable

OSHA Permissible Exposure Limit (PEL)	Shown above.
NIOSH Recommended Exposure Limit (REL)	Shown above.
ACGIH Threshold Limit Value (TLV)	Shown above.
Sara Title III	Not applicable
California Air Resources Board (CARB)	The CARB Air Toxic Control Measures regulation CCR 93120 provides for third party certification and compliance with requirements to reduce allowable formaldehyde emissions from composite wood products. Patriot Timber Products hardwood plywood products are certified to and comply with CARB Phase 1 through year ending 2009 and CARB Phase 2 beginning year 2010.

SECTION 16: OTHER INFORMATION

This fact sheet is for products that have not been finished (coated, laminated or overlaid) or treated, for example with a preservative or fire retardant.

There are several ways to check the workplace for formaldehyde gas and airborne wood dust. In order to be certain of the levels in the air, monitor and compare the results with the relevant occupational exposure levels. Organizations that have set standards or give recommendations for exposure are Occupational Safety and Health Administration (OHS/A), National Institute for Occupational Safety (NIOSH), and the American Conference of Governmental Industrial Hygienists (ACGIH).

Previous Issue: 01/02/2009
Current Issue: 05/07/2010

Important: The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Patriot Timber Products Int., Inc. (PTPI) makes no warranty of any kind, express or implied, concerning the accuracy or completeness of the information and data herein. PTPI will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading. It is incumbent upon the user to obtain the most up-to-date information.