

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Low-Formaldehyde Bonded Wood Products with Patriot Primed[®] Moisture Shield Coating patent pending

Synonyms: Hardwood and Softwood Plywood

Trade Name: IronPly[®] Patriot Primed[®] Soffit U.S Patent No. 8,414,996 and 9,242,391; RevBead[®] Reversible Plywood Beadboard; RevolutionPly[®] Plywood U.S Patent No. 8,414,996 and 9,242,391; SurePly[®] Premium Underlayment

1.2. Intended Use of the Product

Building Material – Industrial and Decorative

1.3. Name, Address, and Telephone of the Responsible Party

Company

Patriot Timber Products, Inc.

117 S. Westgate Drive

Greensboro, NC 27407

www.patriottimber.com

1.4. Emergency Telephone Number

Emergency Number : CHEMTREC: 1-800-424-9300 chemtrec@chemtrec.com

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 1A	H350
STOT SE 3	H335
STOT RE 1	H372
Comb. Dust	

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: May form combustible dust concentrations in air.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H350 - May cause cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, and eye protection.

Precautionary Statements (GHS-US)

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P284 - In case of inadequate ventilation wear respiratory protection.
P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see section 4 on this SDS).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Dust may cause mechanical irritation to eyes, nose, throat, and lungs. Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive. The product may release small quantities of formaldehyde (CAS No. 50-00-0) in gaseous form. Emissions decrease through time as the panels age.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Wood dust, all soft and hard woods	(CAS No) Not applicable	97.78 - 99.72	Comb. Dust Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Water	(CAS No) 7732-18-5	0.098 - 0.777	Not classified
Titanium dioxide	(CAS No) 13463-67-7	0.084 - 0.666	Carc. 2, H351
Vinyl acetate polymer	(CAS No) 9003-20-7	0.0448 - 0.3552	Comb. Dust
Polyvinyl alcohol	(CAS No) 9002-89-5	0.0252 - 0.1998	Comb. Dust
Kaolin	(CAS No) 1332-58-7	0.0168 - 0.1332	Not classified

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Formaldehyde	(CAS No) 50-00-0	< 0.1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350 STOT SE 3, H335 Aquatic Acute 3, H402
Iron oxide yellow	(CAS No) 51274-00-1	0.0056 - 0.0444	Comb. Dust
Iron oxides	(CAS No) 1332-37-2	0.0028 - 0.0222	Not classified
Magnetite (Fe3O4)	(CAS No) 1309-38-2	0.0014 - 0.0111	Not classified
Sodium bicarbonate	(CAS No) 144-55-8	0.00084 - 0.00666	Not classified
Acrylic acid	(CAS No) 79-10-7	0.00056 - 0.00444	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitization. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction. Dust may be harmful or cause irritation.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer. Causes damage to organs through prolonged or repeated exposure. Repeated or prolonged contact with skin may cause dermatitis.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible Dust.

Explosion Hazard: Dust explosion hazard in air.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Toxic fumes may be released. Carbon oxides (CO, CO₂). Hydrogen cyanide. Aldehydes. Organic acids.

Other Information: Risk of dust explosion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Avoid generating dust. Remove ignition sources. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Contact competent authorities after a spill. Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Use only non-sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid creating or spreading dust. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust. Use explosion-proof electrical, ventilating, lighting equipment. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific End Use(s)

Building Material – Industrial and Decorative

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Wood dust, all soft and hard woods		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1 mg/m ³
Formaldehyde (50-00-0)		
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA ACGIH	ACGIH chemical category	dermal sensitizer, Suspected Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (ppm)	0.016 ppm
USA NIOSH	NIOSH REL (ceiling) (ppm)	0.1 ppm
USA IDLH	US IDLH (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
Kaolin (1332-58-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Iron oxides (1332-37-2)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Iron Oxide fume
Acrylic acid (79-10-7)		
USA ACGIH	ACGIH TWA (ppm)	2 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	6 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	2 ppm

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment.

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal Protective Equipment : Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing : Chemically resistant materials and fabrics.
Hand Protection : Wear protective gloves.
Eye Protection : Chemical safety goggles.
Skin and Body Protection : Wear suitable protective clothing.
Respiratory Protection : If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Other Information : When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Solid
Appearance : Light to dark colored granular solid - dependent upon wood species
Odor : Dependent upon wood species
Odor Threshold : No data available
pH : No data available
Evaporation Rate : No data available
Melting Point : No data available
Freezing Point : No data available
Boiling Point : No data available
Flash Point : No data available
Auto-ignition Temperature : No data available
Decomposition Temperature : No data available
Flammability (solid, gas) : No data available
Vapor Pressure : No data available
Relative Vapor Density at 20°C : No data available
Relative Density : No data available
Specific Gravity : < 1 (Varies based on species and moisture content)
Solubility : Water: < 0.1 %
Partition Coefficient: N-Octanol/Water : No data available
Viscosity : No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.
10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials. Sparks, heat, open flame and other sources of ignition. Dust accumulation (to minimize explosion hazard).
10.5. Incompatible Materials: Strong acids, strong bases, strong oxidizers.
10.6. Hazardous Decomposition Products: None expected under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

Formaldehyde (50-00-0)	
LD50 Oral Rat	100 mg/kg
LD50 Dermal Rat	270 mg/kg

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ATE (Gases)	700.00 ppmV/4h
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Kaolin (1332-58-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg
Polyvinyl alcohol (9002-89-5)	
LD50 Oral Rat	> 20 g/kg
Sodium bicarbonate (144-55-8)	
LD50 Oral Rat	4220 mg/kg
Acrylic acid (79-10-7)	
LD50 Oral Rat	1337 mg/kg
LD50 Dermal Rabbit	640 mg/kg
LC50 Inhalation Rat	11.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	3.6 mg/l/4h
LC50 Inhalation Rat	2.8 mg/l/4h

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer.

Wood dust, all soft and hard woods	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Formaldehyde (50-00-0)	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.
Titanium dioxide (13463-67-7)	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Vinyl acetate polymer (9003-20-7)	
IARC group	3
Polyvinyl alcohol (9002-89-5)	
IARC group	3
Acrylic acid (79-10-7)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction. Dust may be harmful or cause irritation.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chronic Symptoms: May cause cancer. Causes damage to organs through prolonged or repeated exposure. Repeated or prolonged contact with skin may cause dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Formaldehyde (50-00-0)	
LC50 Fish 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Sodium bicarbonate (144-55-8)	
LC50 Fish 1	8250 - 9000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	2350 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Acrylic acid (79-10-7)	
LC50 Fish 1	222 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
EC50 Daphnia 1	95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (Algae)	0.13 mg/l

12.2. Persistence and Degradability

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending	
Bioaccumulative Potential	Not established.
Formaldehyde (50-00-0)	
Log Pow	0.35 (at 25 °C)
Acrylic acid (79-10-7)	
Log Pow	0.38 - 0.46 (at 25 °C)

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard Sudden release of pressure hazard
Formaldehyde (50-00-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
SARA Section 313 - Emission Reporting	0.1 %
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Vinyl acetate polymer (9003-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C))
Kaolin (1332-58-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Iron oxide yellow (51274-00-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Iron oxides (1332-37-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyvinyl alcohol (9002-89-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C))
Sodium bicarbonate (144-55-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Magnetite (Fe₃O₄) (1309-38-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Acrylic acid (79-10-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1.0 %

15.2. US State Regulations

Wood dust, all soft and hard woods	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Formaldehyde (50-00-0)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Wood dust, all soft and hard woods	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Formaldehyde (50-00-0)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide (13463-67-7) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Kaolin (1332-58-7) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Acrylic acid (79-10-7) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 03/08/2017
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Muta. 2	Germ cell mutagenicity Category 2
Resp. Sens. 1	Respiratory sensitisation Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage

Low-Formaldehyde Bonded Wood Products with Patriot Primed® Moisture Shield Coating patent pending

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H319	Causes serious eye irritation
H331	Toxic if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)